



TECHNICAL RIDER GOLDEN SPACE

GENERAL INFORMATION & CONTACTS

ADDRESS

August Ortsstraat 20-28
1000 Brussels

RECEPTION

Mo 14:00 - 17:00
Tu - Fri 10:00 - 17:00

CONTACT INFO

Reception / Box Office

+32(0) 2 550 03 50
hello@beursschouwburg.be

Technical Team

techniek@beursschouwburg.be

SAFETY REGULATIONS

The use of fire is not allowed in Beursschouwburg, this includes no candles or cigarettes.

The emergency lights in the building are essential for a safe evacuation and can never be turned off or blocked.

The stair lighting of the tribune in the golden space can never be turned off during a performance.

All textiles used on stage should be accompanied by a fire safety certificate.

Please respect the legal sound limit of max 100 dBA (leq 60 min) and 115 dBC (leq 60 min) at FOH.

TECHNICAL INFORMATION

STAGE

stage

9.7m W x 8.5m D x 9.8m H

prestige

9m W x 6.8m D x 7.2m H

proscenium

8m W x 4.8m H

fire curtain

No scenography under the fire curtain.

flooring

black dancefloor (white floor only available upon request)

CURTAINS

The golden space can be converged into a black box. Please advance.

FLYBARS

stage

17 electrical flybars (8m W; max 300kg)

we only use

2,4,6,8,10,12,14,16 for lights

fixed

16x bars (8m W; max 200kg)

hoists

12x (max 250kg)

FOH

light

4x BNC
4x XLR tielines male/female
4x DMX dubbel
4x Ethercon Cat 6
4x Shuko

sound

4x BNC
4x Ethercon Cat 6
12x XLR tielines male/female
1x LK85

video

8x BNC
4x Ethercon Cat 6

POWER

1x 3F 16A 400V + N

1x 3F 32A 400V + N

1x 3F 63A 400V + N

SOUND

Speakers FOH

6x Nexo GE0-M1210-I (install) flown per side

1x Nexo GE0-M1220-I (downfill) flown per side

4x Nexo L18 SUB

Amps FOH

2x Nexo NXAMP4X4C mk2

Speakers MON

4x l-acoustics LA MTD 112B

Amps MON

1x L'acoustics LA 15A

Mixing desk

Midas M32R / M32 stagerack available upon request

VIDEO

Beamer

1x Panasonic PT-RCQ80BEJ, laser projector 1DLP, 4K ready, 8000 ansi

Projection screen

1x 4m x 6m

Please bring your own laptop and adaptor for HDMI. Several blackmagic converters available

LIGHT

Dimmers

288 dimmers 3Kw

Console

Chamsys MQ 40

FIXTURES

This list is subject to change.

TYPE	POWER	QUANTITY
PC		
ADB C 101 (10°-65°)	1000W	40
ADB C 103 (7°-61°)	1000W	10
ADB A 56 C	650W	10
Fresnel		
ADB F 201 (12°-61°)	2000W	8
Profiles		
ADB DW 105 (15°-38°)	1000W	40
ADB A 59 Z (16°-35°)	650W	12
PAR		
PAR64 (CP60, CP61, CP62)	1000W	80
Cyclorama		
ADB ACP 1000 (with filterframe)	1000W	8
LDR INNO A1000 (with barndoors)	1000W	12
Floor lights		
Sunstrip	1000W	5
Floorcan (PAR64)	1000W	10

LIGHT PLOT

[download dwg file here](#)

